



SUPER BROWN 350 SA

TRONCATRICE SEMIAUTOMATICA


Con variatore continuo di velocità
Per il taglio di tutti i metalli

SUPER BROWN 350/45 SA
per tagli da 0° a 45° Dx

SUPER BROWN 350/60 SA
per tagli da 60° Sx a 45° Dx



* Sono possibili tagli a 45° Dx e 60° Sx solo per il modello 350/60.



D A T I T E C N I C I		mm	110*	115	115	100*
		mm	90*	95	90	80*
		mm	110 x 80*	160 x 90	120 x 80	100 x 80*
		kW	1.5			
		RPM	18 ÷ 93			
		mm	170			
		mm	350			
		kg	200 / 255			
		mm	1000 x 1500 x 1500			
		mm	950			

CAPACITÀ DI TAGLIO

MACCHINA COMPLETA DI:

Mechanism of rotation block test for beveled cuts up to 45° left with lever of locking (for the version 350/45). - Mechanism of rotation block test for beveled cuts up to 60° left and 45° right with lever of locking (for the version 350/60). - Pneumatic chuck and anti-spatter removable. - Pneumatic cylinder of movement test, with brake for the regulation of the speed. - Transmission with double pulley expandable for variable speed from 18 to 93 m/1'. - Test tilting on self-lubricating bearings adjustable. - Inverter of gear. - Pedal of automatic cycle actuation. - Emergency button on the control panel with key. - Lubrication refrigeration system with electric pump. - Liquid refrigerant tank with removable pump for the cleaning of the blade. - Protective cover with millimeter scale. - Support arm with millimeter scale. - Blade disc Ø 350. - Pulley roller. - Pedestal in welded sheet metal of 49 Kg. - Manual of use and maintenance. - Series of keys for maintenance.

ACCESSORI A RICHIESTA:

Roller of loading and unloading of the piece. - Refrigerant liquid.